


Bolt Type Anchor & Chain Shackles



Nominal Shackle Size (in)	Weight (lbs) Bow Type	Weight (lbs) Chain Type	Working Load Limit (tons)	Dimensions (in.)									
				A	B	C	D	E	F	G	I	M	P
1/2	0.79	0.75	2	0.81	0.63	0.50	1.88	0.50	1.19	2.31	1.63	1.81	2.80
5/8	1.68	1.47	3 1/4	1.06	0.75	0.69	2.38	0.63	1.50	2.94	2.00	2.31	3.53
3/4	2.72	2.52	4 3/4	1.25	0.86	0.81	2.81	0.75	1.81	3.50	2.38	2.75	4.07
7/8	3.95	3.85	6 1/2	1.44	1.00	0.97	3.31	0.88	2.09	4.03	2.81	3.19	4.71
1	5.66	5.55	8 1/2	1.69	1.13	1.06	3.75	1.00	2.38	4.69	3.19	3.69	5.31
1 1/8	8.27	7.60	9 1/2	1.81	1.25	1.25	4.25	1.13	2.69	5.16	3.58	4.06	5.90
1 1/4	11.71	10.81	12	2.03	1.38	1.38	4.69	1.25	3.00	5.75	3.94	4.53	6.51
1 3/8	15.83	13.75	13 1/2	2.25	1.50	1.50	5.25	1.38	3.31	6.38	4.38	5.00	7.21
1 1/2	20.80	18.50	17	2.38	1.63	1.62	5.75	1.50	3.63	6.88	4.81	5.38	7.73
1 3/4	33.91	31.40	25	2.88	2.00	2.25	7.00	1.75	4.19	8.86	5.75	6.38	9.05
2	52.25	46.75	35	3.25	2.25	2.40	7.75	2.00	4.81	9.97	6.75	7.25	10.41
2 1/2	98.25	85.00	55	4.13	2.75	3.13	10.50	2.62	5.69	12.87	8.00	9.38	13.56
3	154.00	124.25	85	5.00	3.25	3.62	13.00	3.00	6.50	14.36	8.50	11.00	16.50

Hot dip galvanized forged steel.
Quenched and tempered, with alloy pin.